







VERTICALE



NEW

LE LAVORAZIONI DI SERIE WORKINGS LES TRAVAUX

- 01 Costa diritta - Flat edge - Chant plat
- 02 Smussatura - Beveling - Chanfrein
- 03 Calibratura - Calibrated - Calibrage
- 04 Toro (non lucido) - Bullnose (not polished) - Rond (chant arrondi dé grossé)
- 05 Gocciolatoio inferiore - Under cut - Rainure inférieure
- 06 Slot - Slotting - Fente
- 07 Taglio inclinato - Inclined groove - Coupe incliné



CARATTERISTICHE TECNICHE - TECHNICAL FEATURES - CARACTERISTIQUES TECHNIQUES

DESCRIZIONE - DESCRIPTION - DESCRIPTION	UM	6+2 (6+4)	7+2 (7+4)
Mandrini frontali Polishing spindles Mandrins polissage	n°	6	7
Mandrini lucidatura smussi Bevelling spindles Mandrins pour le polissage des chanfreins	n°	2(4)	2 (4)
Diametro mola spessoramento Diameter of the gauging wheel Diamètre meule calibrage	mm	250 ÷ 350	250 ÷ 350
Diametro mole abrasive lucidanti Diameter of the polishing wheels Diamètre meules abrasives polissantes	mm	130	130
Diametro disco gocciolatoio Diameter of the disc for lower Diamètre disc rainures sup.	mm	250 ÷ 350	250 ÷ 350
Velocità di avanzamento nastro Speed conveyor belt Vitesse avancement bande transporteuse	m/1'	0 ÷ 2	0 ÷ 2
Spessore lavorabile Working thickness Épaisseur usinable	mm	10 ÷ 60	10 ÷ 60
Minima larghezza lavorabile Minimum working width Largeur minimale usinable	mm	50	50
Altezza piano di carico Loading height Hauteur plan de chargement	mm	800	800
Potenza richiesta Power required Puissance demandée	kW	17	18,5
Dimensioni (escluso rulliere) Dimensions (rollers excluded) Dimensions (rouleaux exclus)	m	3200x1250x1370	3420x1250x1370

VERTICALE



COMANDULLI
COSTRUZIONI
MECCANICHE SRL

26012 CASTELLEONE (CR) - ITALY

VIA MEDAGLIE D'ARGENTO, 20

TEL. +39.0374.56161

FAX +39.0374.57888

www.comandulli.it - info@comandulli.it



Member of:



CONFINDUSTRIA MARMOMACCHINE
ASSOMARMOMACCHINE